



## (RVSKS) Rubber feed- and silage scraper

The all scraper. With this scraper; feed can be pulled up, the sand is pushed out of the silage, or moved. And muddy yards and snow can be removed.

- Equipped with 2 pivot points and 4 cylinders, therefore the scraper has a swing angle of 70°.
- The front cylinders are to scrape the yard and sand from the silage and the rear cylinders to scrape the feed. The scraper comes beside the tractor.
- When scraping the silage, it is possible to move the scraper out of the centre by the double pivots. Hereby it is possible to clean the silage further.
- The rubber can move relative to the frame for optimum ground adaptation and uniform wear of the rubber.
- Price exclusive attachment parts.
- The types RVSKS2244 and RVSKS2544 are standard equipped with the option VH.

### For further information:

<https://www.kempmachines.com/rubber-scrapers/rubber-feed--and-silage-scraper?return=/rubber-scrapers>

|   | Types             | Rubber              | Price     |
|---|-------------------|---------------------|-----------|
| ➤ | <b>RVSKS2244</b>  | 2.200 x 400 x 40 mm | € 2.850,- |
| ➤ | <b>RVSKS2544</b>  | 2.500 x 400 x 40 mm | € 2.900,- |
| ➤ | <b>RVSKSL2855</b> | 2.800 x 500 x 50 mm | € 3.095,- |

|   | Options      | Description   | Price   |
|---|--------------|---|---------|
| ➤ | <b>VH</b>    | Adjustable angles   | € 200,- |
| ➤ | <b>SV</b>    | Shock valve for impact protection (2x)                      | € 250,- |
| ➤ | <b>GT</b>    | Pilot operating non-return valve (2x)                       | € 125,- |
| ➤ | <b>3-WEG</b> | 3-way ball valve (at one double-acting function on vehicle) | € 150,- |
| ➤ | <b>6/2</b>   | Electrical 6/2 hydraulic valve                              | € 350,- |

For attachment parts see pages 61-65,